
PUSH FITTINGS AND VALVES



OPERATING PARAMETERS

- 200 PSI MAX Working Pressure
- 200°F MAX Temperature

CERTIFICATIONS & APPROVALS

- Complies with ASSE 1061-2015 (Fittings Only)
- UPC/cUPC Approved
- NSF/ANSI 61 Approved
- NSF/ANSI 14 Approved
- AB1953 Approved



ADVANTAGES

- Durable forged brass body
- Easy to install & remove
- Possible to wet fit
- Compatible with Copper, PEX and CPVC
- Reusable

*For PEX connections, use of included stiffeners is required.





OFFERING INFORMATION

| PART | STYLE | SIZE | CONNECTION |
|----------|-----------------|-----------------|------------|
| 6630-203 | ADAPTER | 1/2 | PUSH x FIP |
| 6630-234 | ADAPTER | 1/2 x 3/4 | PUSH x FIP |
| 6630-204 | ADAPTER | 3/4 | PUSH x FIP |
| 6630-205 | ADAPTER | 1 | PUSH x FIP |
| 6630-103 | ADAPTER | 1/2 | PUSH x MIP |
| 6630-134 | ADAPTER | 1/2 x 3/4 | PUSH x MIP |
| 6630-104 | ADAPTER | 3/4 | PUSH x MIP |
| 6630-154 | ADAPTER | 3/4 x 1 | PUSH x MIP |
| 6630-105 | ADAPTER | 1 | PUSH x MIP |
| 6630-003 | COUPLING | 1/2 | PUSH |
| 6630-004 | COUPLING | 3/4 | PUSH |
| 6630-043 | COUPLING | 3/4 x 1/2 | PUSH |
| 6630-005 | COUPLING | 1 | PUSH |
| 6630-054 | COUPLING | 1 x 3/4 | PUSH |
| 6630-023 | COUPLING | 3/8 x 1/2 | PUSH |
| 6637-003 | COUPLING | 1/2 | PUSH x PB |
| 6637-004 | COUPLING | 3/4 | PUSH x PB |
| 6631-003 | ELBOW | 1/2 | PUSH |
| 6631-004 | ELBOW | 3/4 | PUSH |
| 6631-043 | ELBOW | 3/4 x 1/2 | PUSH |
| 6631-005 | ELBOW | 1 | PUSH |
| 6631-303 | ADAPTER ELBOW | 1/2 | PUSH x FIP |
| 6631-203 | ADAPTER ELBOW | 1/2 | PUSH x MIP |
| 6632-003 | TEE | 1/2 | PUSH |
| 6632-004 | TEE | 3/4 | PUSH |
| 6632-443 | TEE | 3/4 x 1/2 | PUSH |
| 6632-433 | TEE | 3/4 x 1/2 x 1/2 | PUSH |
| 6632-434 | TEE | 3/4 x 1/2 x 3/4 | PUSH |
| 6632-005 | TEE | 1 | PUSH |
| 6633-003 | CAP | 1/2 | PUSH |
| 6633-004 | CAP | 3/4 | PUSH |
| 6633-005 | CAP | 1 | PUSH |
| 6630-303 | REPAIR COUPLING | 1/2 | PUSH |
| 6630-304 | REPAIR COUPLING | 3/4 | PUSH |
| 6630-305 | REPAIR COUPLING | 1 | PUSH |
| 6631-103 | DROP EAR ELBOW | 1/2 | PUSH |
| 1107-063 | BALL VALVE | 1/2 | PUSH |
| 1107-064 | BALL VALVE | 3/4 | PUSH |

| PART | STYLE | SIZE | CONNECTION |
|-------------|-----------------|-----------|------------|
| 1107-065 | BALL VALVE | 1 | PUSH |
| 1190-931HC* | SUPPLY STOP | 1/2 x 1/4 | PUSH x OD |
| 1190-932HC* | SUPPLY STOP | 1/2 x 3/8 | PUSH x OD |
| 1191-931HC* | SUPPLY STOP | 1/2 x 1/4 | PUSH x OD |
| 1191-931HC* | SUPPLY STOP | 1/2 x 3/8 | PUSH x OD |
| 6636-102 | PEX STIFFENER | 3/8 | - |
| 6636-103 | PEX STIFFENER | 1/2 | - |
| 6636-104 | PEX STIFFENER | 3/4 | - |
| 6636-105 | PEX STIFFENER | 1 | - |
| 6636-003 | DISCONNECT CLIP | 1/2 | - |
| 6636-004 | DISCONNECT CLIP | 3/4 | - |
| 6636-005 | DISCONNECT CLIP | 1 | - |